

FO patch cable - FOC-SC:A-ST:A-GZ04/1 - 1413830

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Assembled FO cable, zip cord cable, multi-mode fiberglass $62.5/125 \,\mu m$, OM1, connector: SC duplex/B-FOC (ST), degree of protection: IP20, for installation in cable ducts or control cabinets

Why buy this product

- Multi-mode patch cable for indoor installation
- Ideal for use in distributor systems and for connecting termination devices
- ✓ All components satisfy UL 94, V0
- 2.8 mm single elements made from halogen-free and flame-retardant material
- ☑ Interferometer tests at every stage of the certification process
- Satisfies optical and mechanical industry standards
- Connector with UPC polishing for optimum attenuation values
- Individual test report with ≤ 0.3 dB insertion loss, measured according to IEC 61300-3-4
- Individual test report with ≥ 35 dB return loss, measured according to IEC 61300-3-6

- ☑ Vibration test according to IEC 61300-2-1
- ☑ Tensile strength of the cable connection according to IEC 61300-2-5



Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 009674
GTIN	4055626009674

Technical data

Standards and Regulations

Halogen-free	According to IEC 60754-2
Flammability rating according to UL 94	V0



FO patch cable - FOC-SC:A-ST:A-GZ04/1 - 1413830

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals		
Approvals		
Approvals		
UL Listed		
Ex Approvals		
Approval details		
UL Listed	UL LISTED	http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E308814-20070105

Phoenix Contact 2018 © - all rights reserved http://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany Tel. +49 5235 300

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com