


## Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



8-channel digital output module with spring-cage connection. The power supply unit and the 50-pos. strip are designed redundantly. Suitable for Yokogawa card SDV 531 and SDV 531L.

### Key commercial data

Packing unit	1 pc
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

#### Dimensions

Width	152.5 mm
Height	126 mm
Depth	97 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 55 °C
---------------------------------	------------------

#### General

Nominal voltage $U_N$	30 V DC
Max. current carrying capacity per branch	600 mA
Max. total current of all branches	6.3 A
Mounting position	any
Standards/specifications	Air and creepage distances DIN EN 50178 basic insulation
Pollution degree	2
Surge voltage category	III
Rated surge voltage	0.8 kV
Rated insulation voltage	50 V

# Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

## Technical data

### Connection data for connection 1

Connection name	Field level
Connection method	Spring-cage connection
Number of positions	16
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12

### Connection data for connection 2

Connection name	Control system level
Number of connections	2
Connection method	Yokogawa KS-compatible
Number of positions	50

### Supported controller

Controller	YOKOGAWA ProSafe-RS
- suitable I/O card	SDV531/-L

## Classifications

### eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27069203
eCl@ss 7.0	27069203
eCl@ss 8.0	27069203

### ETIM

ETIM 2.0	EC001434
ETIM 3.0	EC001604
ETIM 4.0	EC001437
ETIM 5.0	EC001437

### UNSPSC

UNSPSC 6.01	30211824
-------------	----------

## Output module - UM-2KS50/ 8DO/RS/Z/C-L/SO225 - 2319485

### Classifications

#### UNSPSC

UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421