

## Specification Sheet

Part Number: 558-00057



<b>Article Number</b>	558-00057
<b>Type</b>	TAG85-100W444SM
<b>Color</b>	White (WH)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>• HellermannTyton SwiftMark Self-Laminating Labels come on rolls for convenient loading and printing.</li><li>• Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time.</li><li>• Labels are UL recognized for indoor and outdoor use to expand application options.</li><li>• HellermannTyton SwiftMark Self-Laminating labels are designed for high speed printing and dispensing to work flawlessly in the SwiftMark applicator and printer.</li></ul>
<b>Quantity Per</b>	reel

**Product Description**

HellermannTyton's self-laminating labels are designed for use in the SwiftMark automatic label applicator and printer. Manufactured in a conformable frosty clear vinyl with good contrast clarity, they are designed with a clear overlap to protect the printed text. The labels come 1 across on a spindle that fits into the applicator. Labels are designed with a special adhesive that bonds quickly to wire and cable using a custom high speed dispensing liner. The printed labels can be used on wires as small as .06" (1.52mm) in diameter and as large as .75" (19mm) in diameter. A UL recognized mark for indoor and outdoor use can be achieved using the TT100 series ribbon (part no. 556-00165). SwiftMark vinyl label meet all the requirements of UL969 - STANDARD FOR MARKING AND LABELING SYSTEMS edition -4. Labels UL recognized under UL file number MH18396. The SwiftMark can accept labels widths that range from .5" (12.7mm) to 2.0" (50.8mm).

**Short Description**

SwiftMark Self-Laminating Label, 1.75" x 1.0" x 3.0", VL, White, 1000/roll

**Global Part Name**

TAG85-100W444SM-100B-WH

**Technical Description**

SwiftMark Self-Laminating Label, 1.75" X 1.0" X 3.0", White

**Variant**

Roller form

**Width W (Imperial)**

1.75

**Width W (Metric)**

44.45

**Bundle Diameter Min (Imperial)**

.14

**Bundle Diameter Min (Metric)**

3.50

**Bundle Diameter Max (Imperial)**

.29

**Bundle Diameter Max (Metric)**

7.60

**Thickness T (Metric)**

35

**Height H (Imperial)**

.50

**Height H (Metric)** 12.70

**Width of Liner (Metric)** 47.62

**Width of Liner (imperial)** 1.875

**Outside Diameter Max(Imperial)** 0.39

**Outside Diameter Min (metric)** 10.1

**Outside Diameter Min(Imperial)** 0.79

**Outside Diameter Max (metric)** 20.2

**Material** Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating

**Material Shortcut** 100B

**Adhesive** Acrylic

**Adhesive Operating Temperature** -40°F to +194°F (-40°C to +90°C)

**Operating Temperature (Metric)** -40°F to +176°F (-40°C to +80°C)

**ROHS Complaint** Yes

**Certification/Specification WEB** UL-Recognized

**UL Recognized (US)** Yes

<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3919102055
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	1.1
<b>Weight (Imperial)</b>	2.42