



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to IEC 60169-10, CECC 22130, US MIL-C-39012

**Documents**

N/A

**Material and plating**

**Connector parts**

- Center contact
- Outer contact
- Outer contact
- Body
- Dielectric

**Material**

- Brass
- Brass
- Brass
- Brass
- PTFE

**Plating**

- AuroDur. gold plated
- AuroDur. gold plated
- AuroDur. gold plated
- AuroDur. gold plated

SMB T-ADAPTOR  
PLUG – PLUG - PLUG**59S301-S00L5****Electrical data**

Impedance	50 $\Omega$
Frequency	DC to 4 GHz
Insulation resistance	$\geq 1 \times 10^3 \text{ M}\Omega$
Center contact resistance	$\leq 5 \text{ m}\Omega$
Outer contact resistance	$\leq 2.5 \text{ m}\Omega$
Test voltage	750 V rms, 50 Hz, at sea level
Working voltage	$\leq 250 \text{ V rms}$ , 50 Hz, at sea level
Contact current	1.5 A DC typ.
RF-leakage	$\geq 55 \text{ dB}$ up to 1 GHz

**Mechanical data**

Mating cycles	$\geq 500$
Center contact captivation: axial	$\geq 10 \text{ N}$
Engagement force	$\leq 63 \text{ N}$
Disengagement force	8 N min. to 63 N max.

**Environmental data**

Temperature range	-55°C to +155°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Moisture resistance	MIL-STD-202, Meth. 106
RoHS	compliant

**Tooling**

N/A

**Suitable cables**

N/A

**Weight**

Weight 2.4 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	14/12/04	Sa. Krautenbacher	20.03.14	d00	14-0352	T. Krojer	20.03.14
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>				Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>			Page 2 / 2