

Part Number: 8259

50 Ohm, RG58 Type, 20 AWG Stranded TC, TC Braid, PVC Jacket



Product Description

50 Ohm, RG-58A/U type, 20 AWG stranded (19x33) .035" tinned copper conductor, polyethylene insulation, tinned copper braid shield (95% coverage), PVC jacket.

Technical Specifications

Nominal Characteristic Impedance

High Frequency (Nominal/Typical) Frequency [MHz] Nom. Insertion Loss

50 Ohm

	nmental Spa	ace:	Indoor (Not R	iser or Plenum)		
Physi	cal Char	acteristics (Ove	erall)			
		`	<u> </u>			
Conduc	tor					
AWG	Stranding	Material	Nominal Diame	ter No. of Coax		
20	Stranded	TC - Tinned Copper	0.035 in	1		
Conduc	ctor Count:		1			
Conduc	ctor Size:		20 AWG			
nsulati	on					
Ma	aterial	Nominal Diameter]			
PE - Po	olyethylene	0.117 in				
	hield Mater		ro/1			
Туре	Mater		[%]			
Braid	TC - Tinned	d Copper 95 %				
Outer J	acket Mate	rial				
	Material	Nominal Diar	meter Nominal V	Vall Thickness		
PVC - I	Polyvinyl Ch	nloride 0.193 in	0.0275 in	0.0275 in		
=lectr	rical Cha	racteristics				
Conduc	ctor DCR					
		or DCR Nominal O	uter Shield DCR	Outer Conductor DCR		
Nomin		tor DCR Nominal Ou 4.1 Ohm/10		Outer Conductor DCR 4.1 Ohm/1000ft		
Nomin 10.8 O	hm/1000ft					
Nomin 10.8 Ol	hm/1000ft	4.1 Ohm/10	00ft			
Nomin 10.8 Ol Capacit Nom. C	hm/1000ft tance		00ft			
Nomin 10.8 Ol Capacit Nom. C 30.8 pF	hm/1000ft tance Capacitance	4.1 Ohm/10	00ft			
Nomin 10.8 Ol Capacit Nom. C	hm/1000ft tance Capacitance	4.1 Ohm/10	00ft			
Nomin 10.8 Ol Capacit Nom. C 30.8 pF Shieldii	hm/1000ft tance Capacitance F/ft ng:	4.1 Ohm/10	00ft			
Nomin 10.8 Ol Capacit Nom. C 30.8 pF Shieldii	hm/1000ft tance Capacitance F/ft ng:	4.1 Ohm/10	00ft			

1 MHz	0.4 dB/100ft
10 MHz	1.5 dB/100ft
50 MHz	3.7 dB/100ft
100 MHz	5.4 dB/100ft
200 MHz	8.1 dB/100ft
400 MHz	12.4 dB/100ft
700 MHz	17.7 dB/100ft
900 MHz	21.1 dB/100ft
1000 MHz	22.8 dB/100ft

Delay

Nominal Delay	Nominal Velocity of Propagation (VP) [%]
1.54 ns/ft	66 %

Voltage

Non-UL Voltage Rating 1400 V RMS

Temperature Range

Non-UL Temp Rating:	75°C
Operating Temp Range:	-30°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	25 lbs/1000ft
Max Recommended Pulling Tension:	39 lbs
Min Bend Radius/Minor Axis:	2 in

Standards

CPR Euroclass:	Eca
RG Type:	58A/U Type
RG / Series Type:	58A/U Type

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	No
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Aerial:	Yes - Black only, when supported by messenger wire	
Suitability - Burial:	No	
Suitability - Hazardous Locations:	No	
Suitability - Indoor:	Yes	
Suitability - Outdoor:	Yes - Black only	

Plenum/Non-Plenum

Plenum (Y/N):	No	

Part Number

Variants

Item #	Color	Footnote
8259 010100	Black	
8259 0101000	Black	С

8259 010500	Black	С
8259 0105000	Black	С
8259 010U1000	Black	
8259 010U500	Black	

Footnote:

C - CRATE REEL PUT-UP.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.