

**Part Number: 8467MN**

SpaceMaker™, (7) 18 AWG (41x34) TC, PP/PVC



[Request Sample](#)

## Product Description

Seven 18 AWG pair stranded (41x34) tinned copper conductors, polypropylene insulation, PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	No. of Conductors
18	41x34	TC - Tinned Copper	7

Conductor Count:	7
Conductor Size:	18 AWG

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.010 in

#### Color Chart

Number	Color
1	Black
2	White
3	Red
4	Dark Green
5	Brown
6	Dark Blue
7	Orange

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.233 in	0.016 in

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR
6.5 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Conductor
14.8 pF/ft

Shielding:	Unshielded
------------	------------

#### Inductance

Nominal Inductance
0.022 $\mu$ H/ft

## Impedance

### Nominal Characteristic Impedance

39 Ohm

## Voltage

### UL Voltage Rating

300 V RMS

## Temperature Range

UL Temp Rating:	80°C
Operating Temp Range:	-20°C To +80°C

## Mechanical Characteristics

Bulk Cable Weight:	69 lbs/1000ft
Max Recommended Pulling Tension:	91 lbs
Min Bend Radius During Installation:	0.930 in
Min Bend Radius (Continuous Flexing):	2.330 in

## Standards

UL AWM Style:	AWM 2937 (300 V 80°C), NFPA 79
---------------	--------------------------------

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes

## Suitability

Suitability - Indoor:	Yes
-----------------------	-----

## Flammability, LS0H, Toxicity Testing

CSA Flammability:	FT2
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Part Number

### Variants

Item #	Color
8467MN 006100	Blue, Light
8467MN 0061000	Blue, Light
8467MN 008100	Gray
8467MN 0081000	Gray
8467MN 004100	Yellow
8467MN 0041000	Yellow

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product

Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.