

<u>5</u>)

_3.02 [0.119]

| Date | SYM | REVISION RECORD | AUTH | DR. | CK. |
|---------|-----|------------------------|------|------|-----|
| 2/25/06 | А | ADDED "ROHS COMPLIANT" | T.B. | B.S. | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

ROHS COMPLIANT

| N0. | PART NAME | MATERIAL | | Tolerance | M | Memory Protection Devices, Inc | | | | |
|-----|---|--|---|-------------------|----------------|--------------------------------|--|-------------|------------------------|--|
| 1 | COVER | PVC COVER OVER FIBERBOARD | 1 | (Except as noted) | | 200 Broad Hollow Road, Farmin | | d. Farmingd | ngdale. New York 11735 | |
| 2 | BLACK WIRE(-) | WIRE(-) 24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C 1 | | decimal | | | | Scale | Drawn By B.S. | |
| 3 | RED WIRE (+) 24 AWG OR 26 AWG, UL-1007, CSA TR-64, 300V, 80°C | | 1 | ±.5 (.020) | | | | | | |
| 4 | FEMALE SNAP | BRASS NICKLE PLATED | 1 | 1.5 (.020) | | | | | Approved By T.B. | |
| 5 | MALE SNAP | BRASS NICKLE PLATED | 1 | Fractional | Title | | | | | |
| | | ± .8 (.030) | 9 VOLT BATTERY SNAP-T STYLE-6" WIRE LEADS | | | | | | | |
| | | Angular | Date | | Drawing Number | | | | | |
| | | ± 3° | 2/25/ | ′06 | BS6T | | | | | |