


PAR	ΓNO.	#B#	"E" REF.		
RMS-01 NATURAL	RMS-01 BLACK	"D" HOLDING DIA.			
N-1	N-1-BK	1/16 [1.6]	.27 [6.7]		
N-2	N-2-BK	1/8 [3.2]	21/64 [8.3]		
N-3	N-3-BK	3/16 [4.8]	25/64 [9.9]		
N-4	N-4-BK	1/4 [6.4]	27/64 [10.7]		
N-5	N-5-BK	5/16 [7.9]	29/64 [11.5]		
N-6	N-6-BK	3/8 [9.5]	31/64 [12.3]		
N-7	N-7-BK	7/16 [11.1]	17/32 [13.5]		
N-8	N-8-BK	1/2 [12.7]	9/16 [14.3]		



SHOWN AS MOLDED

NOTES:

- 1. MATERIAL: NYLON 6/6 UL 94 V-0 (RMS-19).COLOR NATURAL, AVAILABLE BY SPECIAL ORDER ONLY.
 TO ORDER ADD "-19" TO THE END OF PART NUMBER
- TO ORDER ADD "-19" TO THE END OF PART NUMBER.

 2. MATERIAL: NYLON 6/6 UL 94 V-2, UV STABILIZED (RMS-46), COLOR BLACK, AVAILABLE BY SPECIAL ORDER ONLY. TO ORDER REPLACE "-BK" WITH "-UVB"
- 3. RECOMMENDED SCREW SIZE IS #8 [M4], (#4 [M2.5] FOR N-1).

				CABLE CLAMP, N SERIES					DWG IN IN [MM]		
			CREATED USING SOLIDWORKS	FILE #: N-SERIES		DWN: S.K.	APP: R.G.	FINAL			
				TOLERANCES UNLESS NOTED	SHEET:	1 OF 1	SHEET SIZE: A	DT: 04/01/08	CHKD: S.J.	PART #	PRINT TYPE
G	SEE CO 200152 FOR CHANGES	SK	04/03/08		RE: RICHCO, INC.		RICHCO, INC. ENG@RICHCO-INC.COM (773) 539-4060		SEE TABLE		
-	SEE ENGINEERING FOR REV A-F	-		FRAC.=±1/64						= (;A	
REV.	DESCRIPTION	ENGR.	DATE	ANG.=±1°						• • • • • • • • • • • • • • • • • • •	