
KEMET Part Number: PFR5221J63J11L4BULK

(F411JH221J063C)



PFR/F411, Film, Film/Foil Polypropylene, General Purpose, 220 pF, 5%, 63 VDC, 85C, Lead Spacing = 5mm



	Series:	PFR/F411
	Dielectric:	Film/Foil Polypropylene
	Style:	Radial
	Features:	Pulse
<u> </u>	RoHS:	Yes
† G	Lead:	Wire Leads
	Miscellaneous:	An Operating Temperature Up To +105C Is Allowed Under Certain Conditions. Please Consult Kemet For Details.

Dimensions		
L	7.2mm MAX	
Н	6mm MAX	
Т	4.5mm MAX	
S	5mm -0.4mm	
LL	4mm +1mm	
F	0.5mm +/-0.05mm	
G	0.5mm NOM	

Packaging Specifications		
Packaging:	Bulk, Bag	
Packaging Quantity:	1000	

Specifications		
Capacitance:	220 pF	
Capacitance Tolerance:	5%	
Voltage AC:	40 VAC	
Voltage DC:	63 VDC	
Temperature Range:	-55/+100C	
Rated Temperature:	85C	
Dissipation Factor:	0.04% 1kHz, 0.04% 10kHz, 0.05% 100kHz	
Insulation Resistance:	136363.6364 GOhms	
Max dV/dt:	1000 V/us	
Inductance:	6 nH	

General Information

KEMET

Supplier:

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

